

## **CP-1542-46**

### **PRODUCT DESCRIPTION**

CP-1542-46 is custom-blended polyalkylene glycol (PAG)/ ester rotary screw air compressor lubricants. This formulation offers improved lubrication at high and low temperature, reduced volatility, and high viscosity index, plus excellent corrosion protection.

CP-1542-46 (typical properties shown below) is long life lubricants formulated with rust and oxidation inhibitors. Other viscosities are available for specific applications.

CP-1542-46 will not leave behind carbon residue/ varnish when it oxidizes as compared to hydrocarbon based products.

<b>TYPICAL PROPERTIES*</b>	<b>CP-1542-46</b>
Viscosity@40°C,cSt, ASTM D445	48.25
Viscosity@100°C,cSt	9.38
Viscosity@100°F,SUS	244
Viscosity@210°F,SUS	57.8
Viscosity Index ASTM D2270	182
Density, g/ml, 20°F	0.974
Flash Point, C.O.C., °F ASTM D92	525°F
Fire Point, C.O.C., °F ASTM D92	540°F
Color	Water White
Pour Point	-48°C
Copper Corrosion	1a

\*These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)