

CP-4126-150

PRODUCT DESCRIPTION

CP-4126-150 is a diester based synthetic lubricants specially formulated for rotary vane or reciprocating air compressor applications. Benefits of using these lubricants include:

- Eliminate the formation of sludge, varnish and other deposits
- Extended lubricant life
- Superior demulsibility
- Wide operating temperature range

TYPICAL PROPERTIES*

CP-4126-150

Viscosity @ 40°C, cSt, ASTM D445	148
Viscosity @ 100°C, cSt	14.23
Viscosity @ 100°F, SUS	784
Viscosity @ 210°F, SUS	76.6
Viscosity Index, ASTM D2270	93
Density, lb/gal, 60°F, ASTM D4052	7.77
Pour Point °F (°C), ASTM D97	-38(-39)
Flash Point, C.O.C., °F (°C), ASTM D92	475(246)
Fire Point, C.O.C., °F (°C), ASTM D92	510 (266)
Specific Gravity, ASTM D4052	0.931

*These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com