

CP-4600-150-F

PRODUCT DESCRIPTION

CP-4600-F Series are custom-blended polyalphaolefin (PAO)synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4600-F Series (typical properties shown below) are long life lubricants formulated with rust and oxidation inhibitors for flooded screw compressors.

CP-4600-F Series are authorized by USDA for use in federally inspected meat and poultry plants (H-1). Complies with FDA 21 CFR 178.3570 – Lubricants with Incidental Food Contact.

TYPICAL PROPERTIES**

CP-4600-150-F

Viscosity @ 40°C, cSt, ASTM D445	147.7
Viscosity @ 100°C ,cSt	18.2
Viscosity @ 100°F	164.8
Viscosity @210°F	18.7
Viscosity Index ASTM D2270	138
Density, lb/gal, 60°F	7.04
Pour Point °F (°C) ASTM D97	-49(-45)
Flash Point, C.O.C °F (°C) ASTM D92	530(277)
Fire Point, C.O.C °F (°C) ASTM D92	580(304)
Specific Gravity, ASTM D1298	0.845

** These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com