

CP-4600-320-F

PRODUCT DESCRIPTION

CP-4600-F Series are custom-blended polyalphaolefin (PAO)synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4600-F Series (typical properties shown below) are long life lubricants formulated with rust and oxidation inhibitors for flooded screw compressors.

CP-4600-F Series are authorized by USDA for use in federally inspected meat and poultry plants (H-1). Complies with FDA 21 CFR 178.3570 – Lubricants with Incidental Food Contact.

TYPICAL PROPERTIES**

CP-4600-320-F

| | |
|-------------------------------------|----------|
| Viscosity @ 40°C, cSt, ASTM D445 | 320.0 |
| Viscosity @ 100°C ,cSt | 33.0 |
| Viscosity @ 100°F | 359.9 |
| Viscosity @210°F | 34.0 |
| Viscosity Index ASTM D2270 | 145 |
| Density, lb/gal, 60°F | 7.08 |
| Pour Point °F (°C) ASTM D97 | -38(-39) |
| Flash Point, C.O.C °F (°C) ASTM D92 | 540(282) |
| Fire Point, C.O.C °F (°C) ASTM D92 | 592(311) |
| Specific Gravity, ASTM D1298 | 0.850 |

** These values are not intended for use in preparing specifications.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com