

## **CP-4601-5**

### **PRODUCT DESCRIPTION**

CP-4601 Series are custom-blended polyalphaolefin (PAO) synthetic hydrocarbon fluids giving improved lubrication at high and low temperatures, reduced volatility, and compatibility with mineral oils and equipment designed for use with mineral oils.

CP-4601 Series (typical properties shown below) are long life lubricants formulated with rust and oxidation inhibitors. Other viscosities are available for specific applications.

CP-4601 Series are authorized by USDA for use in federally inspected meat and poultry plants with no possibility of food contact (H-2)

<b>TYPICAL PROPERTIES*</b>	<b>CP-4601-5</b>
Viscosity@40°C,cSt,ASTM D445	6.94
Viscosity @100°C,cSt	2.41
Viscosity @100°F	7.32
Viscosity @210°F	2.45
Viscosity Index ASTM D2270	202
Density lb/gal, 60°F	6.76
Pour point°F (°C) ASTM D97	-100(-73)
Flash point C.O.C.,°F (°C) ASTM D92	330(165)
Fire point C.O.C.,°F (°C) ASTM D92	350(176)
Specific Gravity, ASTM D1298	0.812

\* These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)