

CPI Food Machinery Oil 220

FMO 220

Food Grade Custom-Blended Lubricants

PRODUCT DESCRIPTION

CPI Food Machinery Oil series products are custom-blended highly refined, chemically inert lubricants with additives for improved lubricity and defoaming characteristics. Widely used for applications in the food processing industries where the lubricant has indirect contact with food substances.

APPLCATIONS

- Energy saving gear application
- Lubricant for vacuum pumps
- General purpose lubricant for long life and antiwear
- Lubricant/coolant for compressors
- Lubricant and sealing fluid for rotary mechanical shaft seals of processing pumps and agitated kettles

CPI Food Machinery Oil series products meet 21 CFR 178.3570 requirements for lubricants with the possibility of indirect food contact. Authorized by USDA for use in Federally inspected meat and poultry plants.

TYPICAL PROPERTIES*

FMO 220

| | |
|-------------------------------|---------|
| Viscosity@40°C,cSt, ASTM D445 | 218 |
| Viscosity @100°C °C,cSt | 19.9 |
| Viscosity @100°F | 248.5 |
| Viscosity @210°F | 20.55 |
| Viscosity Index ASTM D2270 | 100 |
| Density, 1b/gal, 60 °C | 7.2 |
| Pour point°F (°C) | 20 (-6) |

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com

| | |
|--------------------------------------|-----------|
| Flash point C.O.C., °F (°C) ASTM D92 | 490 (254) |
| Fire point C.O.C., °F (°C) ASTM D92 | 510 (266) |
| Specific Gravity, ASTM D1298 | 0.86 |

*These values are not intended for use in preparing specifications

Shanghai PingYiao Trading CO., Ltd.

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.com

E-mail: info@pingyiao.com