

## **CP-1516-150**

### **Hydrocarbon Gas Compressor Lubricant**

#### **PRODUCT DESCRIPTION**

CP-1516-150 product is unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of CP-1516-150 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

#### **APPLICATIONS**

Propane refrigeration compressor lubrication.

Natural gas and other light hydrocarbon compressor applications.

<b>TYPICAL PROPERTIES*</b>	<b>CP-1516-150</b>
Viscosity@40°C, cSt, ASTM D445	153.0
Viscosity@100°C, cSt	23.5
Viscosity@100°F	156.0
Viscosity@210°F	24.0
Viscosity Index ASTM D2270	196
Density, lb/gal, 60°F	8.29
Pour Point °F (°C) ASTM D97	-30(-34)
Flash Point, C.O.C., °F (°C) ASTM D92	500(260)
Fire Point, C.O.C., °F (°C) ASTM D92	540(282)
Specific Gravity, ASTM D1298	0.995

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)