

CP-1516-68

Hydrocarbon Gas Compressor Lubricant

PRODUCT DESCRIPTION

CP-1516-68 product is unique custom blend of polyalkylene glycols with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of CP-1516-68 lubricant to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

APPLICATIONS

Propane refrigeration compressor lubrication.

Natural gas and other light hydrocarbon compressor applications.

TYPICAL PROPERTIES*	CP-1516-68
Viscosity@40°C,cSt, ASTM D445	61.5
Viscosity@100°C,cSt	10.8
Viscosity@100°F	67.2
Viscosity@210°F	11.0
Viscosity Index ASTM D2270	168
Density, lb/gal, 60°F	8.25
Pour Point °F (°C)ASTM D97	-55(-48)
Flash Point, C.O.C., °F (°C)ASTM D92	425(218)
Fire Point, C.O.C., °F (°C)ASTM D92	465(241)
Specific Gravity, ASTM D1298	0.989

Shanghai PingYiao Trading CO., Ltd.

Adress: Xuhui District, Shanghai Caoxi Yinhai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: www.pingyiao.com

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: info@pingyiao.com