

## CP-RPAG-354-125

### PRODUCT DESCRIPTION

RPAG polyglycol lubricants are specially formulated for use in vehicle air conditioning systems running on R134a. Developed for original fill and top up RPAG lubricants feature excellent chemical and thermal stability, improved wear performance and extended compressor life. Backed by global approvals from major car manufacturers you can be assured of getting the right lubricant whatever the application.

TYPICAL PROPERTIES	CP-RPAG-125
Viscosity @40°C,cSt, ASTM D445	134.6
@100°C	25.1
@100°F	146.3
@210°F	25.6
Viscosity Index ASTM D2270	221
Density (1b/gal) 60°F	8.780
Pour Point °F (°C) ASTM D97	-44(-42)
Flash Point, C,O,C °F (°C) ASTM D92	485(251)
Fire Point C,O,C °F (°C) ASTM D92	525(273)
Specific Gravity,ASTM D1298	1.055
TAN(mgKOH/g) ASTM D974	0.40
Dielectric Strength ASTM D877	ND
Copper Strip Test ASTM D130	1a

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: [www.pingyiao.com](http://www.pingyiao.com)E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)