

CP-RPAG-354-150

PRODUCT DESCRIPTION

RPAG polyglycol lubricants are specially formulated for use in vehicle air conditioning systems running on R134a. Developed for original fill and top up RPAG lubricants feature excellent chemical and thermal stability, improved wear performance and extended compressor life. Backed by global approvals from major car manufacturers you can be assured of getting the right lubricant whatever the application.

TYPICAL PROPERTIES	CP-RPAG-150
Viscosity @40°C,cSt, ASTM D445	150.8
@100°C	17.5
@100°F	787.7
@210°F	90.1
Viscosity Index ASTM D2270	127
Density (1b/gal) 60°F	8.51
Pour Point °F (°C) ASTM D97	-19 (-28)
Flash Point, C,O,C °F (°C) ASTM D92	375 (190)
Fire Point C,O,C °F (°C) ASTM D92	400 (204)
Specific Gravity,ASTM D1298	1.02
Moisture, ppm, ASTM D1744	<200
Dielectric Strength ASTM D877	27.0
Copper Strip Test ASTM D130	1a

Shanghai PingYiao Trading CO., Ltd.

Tel: 86-21-64705533

Adress: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Fax: 86-21-64705533-209

Website: www.pingyiao.comE-mail: info@pingyiao.com