

## CP-RPAG-354-46

### PRODUCT DESCRIPTION

RPAG polyglycol lubricants are specially formulated for use in vehicle air conditioning systems running on R134a. Developed for original fill and top up RPAG lubricants feature excellent chemical and thermal stability, improved wear performance and extended compressor life. Backed by global approvals from major car manufacturers you can be assured of getting the right lubricant whatever the application.

TYPICAL PROPERTIES	CP-RPAG-46
Viscosity @40°C, cSt, ASTM D445	46.52
@100°C	9.47
@100°F	236.3
@210°F	58.1
Viscosity Index ASTM D2270	193
Density (lb/gal) 60°F	8.14
Pour Point °F (°C) ASTM D97	-44(-42)
Flash Point, C, O, C °F (°C) ASTM D92	315(157)
Fire Point C, O, C °F (°C) ASTM D92	335(1680)
Specific Gravity, ASTM D1298	0.978
TAN(mgKOH/g) ASTM D974	0.025
Dielectric Strength ASTM D877	34.8
Copper Strip Test ASTM D130	1a

Shanghai PingYiao Trading CO., Ltd.

Address: Xuhui District, Shanghai Caoxi Yin Hai Building, A1207 Room, No. 250

Telephone helpline: 15900706965

Website: [www.pingyiao.com](http://www.pingyiao.com)

Tel: 86-21-64705533

Fax: 86-21-64705533-209

E-mail: [info@pingyiao.com](mailto:info@pingyiao.com)